

Specification sheet

XD 220

FA 4X2 Rigid, Electric



ENGINES

XD Electric 170 PACCAR EX-D1 (170 kW /	210 kWh 315 kWh 420 kWh 525 kWh)
XD Electric 220 PACCAR EX-D1 (220 kW /	315 kWh 420 kWh 525 kWh)
XD Electric 270 PACCAR EX-D1 (270 kW /	315 kWh 420 kWh 525 kWh)
XD Electric 270 PACCAR EX-D2 (270 kW /	315 kWh 420 kWh 525 kWh)
XD Electric 310 PACCAR EX-D2 (310kW /	420 kWh 525 kWh)
XD Electric 350 PACCAR EX-D2 (350kW /	420 kWh 525 kWh)

GVM¹⁾

19000 kg
Max. front 7000 kg
Max. rear 13000 kg

GCM²⁾

21500 kg

067F0100AAAA - 202513C - 06-12-2024

Greece, ERGOTRAK, www.daftrucks.gr

CAB EXTERIOR

Luxurious Day Cab with unrivalled aerodynamics for fuel efficient driving and low CO2 emissions. The huge and deep frontscreen, curved at the sides combined with large side windows offer an unsurpassed direct view for the driver, to enhance road safety. Cab length: 2030 mm; cab width: 2500 mm.; Cab suspension mechanical; LED head lights; DAF Corner View.

Optional

07018 Sleeper Cab	01836 LED Skylights
06244 Sleeper High Cab	00949 LED Skylights; aux. LED lights on cab rf, prepared
02889 Chassis front execution: no bottom plate	01925 Two LED work lamps for cab rear wall
02952 Chassis front execution: bottom plate aero	01891 Hazard beacons on cab front, prepared
07586 Chassis front execution: robust	06629 Two hazard beacon lights
01226 Cab suspension air	03232 Front windscreen with solar control foil
03358 External sun visor	03317 Rear window: double glass
03922 Fog lights front	07343 Kerb view window co-driver door
00936 Auxiliary LED lights on cab roof, prepared	01362 DAF Digital Vision System

AERODYNAMICS

Optional

00008 Adj. roof air deflector short Sleeper High Cab	00082 Adj. roof air deflector for Day Cab
00124 Adj. rf air defl.long mid >4m(!) Sleeper High Cab	00097 Adj. roof air deflector for Sleeper Cab
01538 Adj. roof air defl. long high >4m(!) Sleeper High	00020 Adj. roof air deflector long low Sleeper High Cab
02662 Adj. roof air defl. long mid XD Sleeper High Cab	

COLOURS

Cab colour E1980 Crystal White; Chassis colour grey.; Colour of bumper: Crystal White.

CAB INTERIOR

Cab interior trim colour: Luxury; Dashboard finish: Vision; Cab interior decoration: Hexagon; Driver seat: Comfort Air; Co-driver seat: cinema with fabric cover; No dashboard table; Storage compartment in centre; Automatic Temperature Control and airco; Auxiliary cab heater (water).

Optional

02354 Steering wheel with silver accents	02117 Third seat
02355 Steering wheel, leather	02837 Dashboard table
02353 Cab interior decoration: Argenta	03948 Single drawer
02350 Cab interior decoration: Natura	03954 Refrigerator
07733 Driver seat: Luxury Air	02838 Foam mattress for lower bunk
07736 Driver seat: Super Air	02854 Xtra Comfort mattress for lower bunk
07737 Driver seat: Xtra Leather Air	01775 Xtra Comfort mattress with topper for lower bunk
09541 Arm rest driver seat	06970 Automatic Cab Climate Control
01740 Arm rest at both sides of the driver seat	

COMMUNICATION AND DRIVING MANAGEMENT

PACCAR Connect; Tachograph digital, Stoneridge 1C version G2V2; Speed limiter setting 85/90 km/h; DAF Infotainment Luxury with Luxury speakers; Adaptive Cruise Control with FCW and AEBS-3; Driver Performance Assistant.

Optional

09681 Preparation for Maut	01915 DAF Infotainment System: Luxury Plus
06211 DAF Infotainment System with FM/DAB/DAB+ radio	06991 Predictive Cruise Control
03470 DAF Infotainment System: Exclusive, prepared	06992 Predictive Cruise Control lite

SAFETY AND SECURITY

Lane Departure Warning System; Vehicle Stability Control (VSC); Basic engine immobiliser system; No EC-ADR packages; DAF Side & Turn Assist.

Optional

08631 Air bag (driver) and 2 seat belt tensioners
--

SUSPENSION AND AXLES

Front: 8.00 t, parabolic, 163N; Rear axle load 13.00 t; Rear: air suspension, SR1344; No lifting device.

Optional

06257 Front axle load 9.00 t	04647 Front springs air
06095 Front axle load 10.00 t	08191 Axle load monitoring

WHEELS AND TYRES

Driven rear axle(s): 315/70R22.5; F1,315/70R22.5GO FMXSE 156/150 L Steering BBA 3P; R1,315/70R22.5GO FMXDE 154/150 L Traction BBA 3P.

Optional

16152 Tyre makes and types

DRIVELINE

Electric motor type EX-D1; 220 kW; 150 kW DC charging; Battery Electric Vehicle; Rear axle ratio 2.05.

Optional

01656 Electric motor type EX-D2	01749 Charging: 150 kW DC + 22 kW AC
01664 170 kW	01756 325 kW DC charging
01686 270 kW	03677 Charging: 325 kW DC + 22 kW AC
01691 310 kW	01514 Urge-to-move
01692 350 kW	02843 Mechanical differential lock

BRAKE SYSTEM

Ventilated disc brakes front and rear. Dual circuit air system with electronic control (EBS). Electric driven, water cooled air compressor with automatic air heated dryer..

Optional

04901 Spring brake cylinders on the first front axle

CHASSIS

Wheelbase 4.30 m / rear overhang 1.80 m; Side member height 260 mm; Standard component location; 3 HV battery packs; HV battery pack left, position 2; HV battery pack right, position 2; Front underrun protection (FUP); Spray suppression.

Optional

- | | |
|---|--|
| 02601 Side member height 310 mm | 01762 HV battery packs left, positions 2 and 3 |
| 01696 2 HV battery packs | 01779 HV battery pack right, position 1 |
| 01699 4 HV battery packs | 01791 HV battery packs right, positions 1 and 2 |
| 01701 5 HV battery packs | 01799 HV battery packs right, positions 2 and 3 |
| 01634 HV battery pack left, position 1 | 01658 No HV battery packs right |
| 01759 HV battery packs left, positions 1 and 2 | 16157 Fuel tanks, material and sizes |

DRAWBAR AND TRAILER EQUIPMENT

Closing member D-value = 0kN.

Optional

- | | |
|--|--|
| 07033 Trailer coupling Ringfeder D=13.7 | 08027 Trailer coupling Rockinger D=20.0 |
| 07034 Trailer coupling Ringfeder D=20.0 | 04659 Trailer cable EBS |
| 08026 Trailer coupling Rockinger D=13.0 | |

BODIES AND PREPARATIONS FOR BODYING

Application connector chassis.

Optional

- | | |
|---|------------------------------------|
| 09421 Additional spare wiring | 08121 Tail lift application |
| 09240 Application connector for refuse collector | |

POWER TAKE-OFF (PTO)

Optional

- | | |
|---|---|
| 01809 E-PTO socket 650V DC < 25 kW | 04320 E-PTO socket 650V DC < 90 kW |
|---|---|

24V POWER SUPPLY

Batteries 2x 175 Ah..

Optional

- | | |
|---|--------------------------------|
| 07671 Batteries 2x210Ah AGM C-type | 06440 Batteries 2x230Ah |
|---|--------------------------------|

GVM AND GCM

Chassis weight related technical GVM max 20500 kg; Driveline related max GCM 21500 kg.

Optional

- | | |
|---|---|
| 01933 Driveline related max GCM 42000 kg | 02200 Driveline related max GCM 46000 kg class 2 |
| 01937 Driveline related max GCM 46000 kg | 03675 Driveline related max GCM 50000 kg class 3 |

APPLICATION CONDITIONS

Optional

- | | |
|-----------------------------------|---------------------------------------|
| 02260 Extra cab insulation | 06614 Anti-dust blow-up shield |
|-----------------------------------|---------------------------------------|

SERVICE AND MAINTENANCE

Standard Warranty takes care of 1 year complete vehicle as supplied by the OEM (excl. real wear parts), 2nd year driveline and 1st year breakdown.; ITS service.

VEHICLE DELIVERY

Minimum toolkit.

Optional

- 07569** Lifting jack

OPTION PACKAGES


Optional

- | | |
|--------------------------|-----------------------------------|
| 17448 Safety pack | 17595 Executive Pack XD/XF |
|--------------------------|-----------------------------------|

Go to [DAF.com](https://www.daf.com) to configure your own perfect DAF.

XD 220

FA 4X2 Rigid, Electric



	Wheelbase - AE		Unladen weight ⁹⁾			Gross Carrying Capacity			Variable dimensions									
	WB	AE ⁵⁾	Front	Rear	Total	Front	Rear	Total	AC	CB ⁶⁾	CH ⁷⁾	BL ⁸⁾	BL	TL	HA ⁹⁾	HA ¹⁰⁾	TK ¹¹⁾	TW ¹²⁾
DAY CAB	3,90	1,30	5610	3065	8675	1390	9935	10325	0,50	0,07	2,06	5,09	5,41	6,73	0,97	0,94	13,76	15,14
	4,30	1,80	5744	3042	8787	1256	9958	10213	0,50	0,07	2,06	5,81	6,17	7,63	0,97	0,94	14,79	16,20
	4,50	1,95	5826	3036	8862	1174	9964	10138	0,50	0,07	2,06	6,18	6,56	7,98	0,97	0,94	15,31	16,73
	4,70	2,05	5877	3003	8880	1123	9997	10120	0,50	0,07	2,06	6,54	6,94	8,28	0,97	0,94	15,83	17,26
	4,90	2,35	5926	3006	8932	1074	9994	10068	0,50	0,07	2,06	6,91	7,32	8,78	0,97	0,94	16,35	17,78
	5,10	2,75	5959	3019	8978	1041	9981	10022	0,50	0,07	2,06	7,26	7,70	9,38	0,97	0,94	16,87	18,31
	5,40	2,65	6036	2962	8998	964	10038	10002	0,50	0,07	2,06	7,82	8,28	9,58	0,97	0,94	17,66	19,11
	5,70	2,85	6122	2990	9112	878	10010	9888	0,50	0,07	2,06	8,39	8,87	10,08	0,97	0,94	18,44	19,90
	6,10	2,80	6205	2939	9143	795	10061	9857	0,50	0,07	2,06	9,14	9,66	10,43	0,97	0,94	19,49	20,96
SLEEPER CAB	3,90	1,30	5715	3069	8784	1285	9931	10216	0,83	0,07	2,06	4,49	4,80	6,73	0,97	0,94	13,75	15,14
	4,30	1,80	5850	3046	8896	1150	9954	10104	0,83	0,07	2,06	5,22	5,57	7,63	0,97	0,94	14,79	16,20
	4,50	1,95	5931	3039	8971	1069	9961	10029	0,83	0,07	2,06	5,59	5,97	7,98	0,97	0,94	15,31	16,73
	4,70	2,05	5983	3006	8989	1017	9994	10011	0,83	0,07	2,06	5,96	6,36	8,28	0,97	0,94	15,83	17,26
	4,90	2,35	6032	3009	9041	968	9991	9959	0,83	0,07	2,06	6,32	6,74	8,78	0,97	0,94	16,35	17,78
	5,10	2,75	6065	3022	9087	935	9978	9913	0,83	0,07	2,06	6,68	7,11	9,38	0,97	0,94	16,87	18,31
	5,40	2,65	6142	2965	9107	858	10035	9893	0,83	0,07	2,06	7,24	7,70	9,58	0,97	0,94	17,66	19,11
	5,70	2,65	6234	2961	9195	766	10039	9805	0,83	0,07	2,06	7,83	8,32	9,88	0,97	0,94	18,44	19,90
	6,10	2,80	6311	2941	9252	689	10059	9748	0,83	0,07	2,06	8,57	9,10	10,43	0,97	0,94	19,49	20,96
SLEEPER HIGH CAB	3,90	1,30	5746	3068	8814	1254	9932	10186	0,83	0,07	2,54	4,50	4,83	6,73	0,97	0,94	13,75	15,14
	4,30	1,80	5881	3045	8926	1119	9955	10074	0,83	0,07	2,54	5,23	5,59	7,63	0,97	0,94	14,79	16,20
	4,50	1,95	5962	3039	9001	1038	9961	9999	0,83	0,07	2,54	5,61	5,99	7,98	0,97	0,94	15,31	16,73
	4,70	2,05	6014	3005	9019	986	9995	9981	0,83	0,07	2,54	5,98	6,38	8,28	0,97	0,94	15,83	17,26
	4,90	2,35	6063	3008	9071	937	9992	9929	0,83	0,07	2,54	6,34	6,76	8,78	0,97	0,94	16,35	17,78
	5,10	2,75	6096	3021	9117	904	9979	9883	0,83	0,07	2,54	6,71	7,14	9,38	0,97	0,94	16,87	18,31
	5,40	2,65	6172	2964	9137	828	10036	9863	0,83	0,07	2,54	7,27	7,73	9,58	0,97	0,94	17,66	19,11
	5,70	2,65	6264	2961	9225	736	10039	9775	0,83	0,07	2,54	7,85	8,34	9,88	0,97	0,94	18,44	19,90
	6,10	2,80	6342	2940	9282	658	10060	9718	0,83	0,07	2,54	8,60	9,13	10,43	0,97	0,94	19,49	20,96

OTHER DIMENSIONS VA: 1,53 HV¹³⁾: 0,95 HV¹⁴⁾: 0,88 RB: 0,79 SB: 1,82 TB¹⁵⁾: 2,48

- 1) GVM in conformity with registration documents.
- 2) GCM in conformity with registration documents.
- 3) Axle load with standard tyre size.
- 4) Chassis and cab weight calculated with: Standard specification items only with driver of (0) kg, tolerance ± 3%. Changing of the specification can have major impact on vehicle weight
- 5) Other AE dimensions may be available for shown WB. Modify rear overhang to the calculated body length.
- 6) Based on basic specification.
- 7) Cab height is measured from frame member to closed cabin roof hatch.

- 8) Calculate customer specific body length with TOPEC. Body lengths shown based on evenly distributed load at max axle load.
- 9) Unladen height at centre of driven axle(s).
- 10) Laden height at centre of driven axle(s).
- 11) TK = turning circle between kerbs.
- 12) TW = turning circle between walls.
- 13) Unladen height at centre of front axle(s).
- 14) Laden height at centre of front axle(s).
- 15) TB is overall width at rear. (At centre of front axle 255).

Depending on the vehicle configuration a specific option may not be possible. The availability and specification of this vehicle may differ per country. For further information please contact the DAF organisation. Pictures and technical illustrations are not binding in detail and can differ from the standard specification. Subject to modification without prior notice.